

PF	Product Fiche according to (EU) No 65/2014			
S	Supplier's name or trade mark	PANDO / P725		
M	Model identifier			
	Annual Energy Consumption	AEC hood	49.0	kWh/a
	Energy Efficiency Class	EEI class	A	
	Fluid Dynamic Efficiency	FDE hood	29.7	%
	Fluid Dynamic Efficiency class	FDE class	A	
	Light Efficiency	LE hood	42	lux/W
	Lighting Efficiency Class	LE class	A	
	Grease Filtering Efficiency	GFE hood	81.1	%
	Grease Filtering Efficiency class	GFE class	C	
	Minimum Air Flow in normal use	Q min	286.3	m ³ /h
	Maximum Air Flow in normal use	Q max	608.5	m ³ /h
	Air Flow at intensive/boost setting	Q boost	756.5	m ³ /h
	A-weighted Sound Power Emission at minimum speed	SPE min	48	dB(A) re 1pW
	A-weighted Sound Power Emission at maximum speed	SPE max	62	dB(A) re 1pW
	A-weighted Sound Power Emission at intensive or boost speed	SPE boost	68	dB(A) re 1pW
	Power consumption off mode	Po	0.00	W
	Power consumption in standby mode	Ps	0.44	W
Additional Information according to (EU) No 66/2014				
	Time increase factor	f	0.9	
	Energy Efficiency Index	EEI hood	51.3	%
	Measured air flow rate at best efficiency point	Q bep	367.9	m ³ /h
	Measured air pressure at best efficiency point	P bep	417	Pa
	Maximum air flow	Q max	608.5	m ³ /h
	Measured electric power input at best efficiency point	W bep	143.3	W
	Nominal power of the lighting system	WL	3.0	W
	Average illumination of the lighting system on the cooking surface	E middle	127	lux