



<b>BO420102</b>
<b>Oven 400 series</b>
<b>Full glass door in Gaggenau Anthracite</b>
<b>Width 60 cm</b>
<b>Right-hinged</b>
<b>Controls at the top</b>



Handleless door / automatic door opening  
 Pyrolytic system  
 9 heating methods, with baking stone function  
 TFT touch display  
 Panel-free appliance with surface control module  
 Electronic temperature control from 50 °C to 300 °C  
 Net volume 76 litres

#### Heating methods

Hot air.  
 Eco hot air. Top + bottom heat. Top heat. Bottom heat. Hot air + bottom heat. Full surface grill + circulated air. Full surface grill. Baking stone function.

#### Handling

Automatic door opening.  
 Rotary knob and TFT touch display operation.  
 Clear text display.  
 Option to save individual recipes. Information key with use indicators. Side-opening door opens up to 180° angle.

#### Features

Baking stone socket.  
 Actual temperature display.  
 Rapid heating.  
 Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer (certified by Star-K).  
 60 W halogen light on the top.  
 Enamelled side shelf supports with 4 tray levels, pyrolysis-safe.

#### Selected digital services (Home Connect)

Remote control and monitoring. Recipes.  
 Home network integration for digital services (Home Connect) either via cable connection LAN (recommended) or wireless via WiFi.  
 The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

#### Safety

Thermally insulated door with quadruple glazing.  
 Child lock.  
 Safety shut-off.  
 Cooled housing with temperature protection.

#### Cleaning

Pyrolytic system.  
 Gaggenau enamel.  
 Heated catalyser to clean the oven air.

#### Planning notes

Door hinge not reversible.  
 The facade of the appliance extends 47 mm from the furniture cavity.  
 If the handle (optional accessory) is retrofitted, the outer edge of the door handle extends 94 mm from the furniture cavity.  
 Consider the overhang, incl. the door handle where applicable, when planning to open drawers next to the appliance.  
 When planning a corner solution, pay attention to the side-opening door and the minimum required distance to the wall.

#### Characteristics

<b>Gross weight</b>	58.5
<b>Color / Material Front</b>	Anthracite
<b>Built-in / Free-standing</b>	Built-in
<b>Integrated Cleaning system</b>	Pyrolytic
<b>Min. required niche size for installation (HxWxD)</b>	590-590 x 560-560 x 550
<b>Dimensions</b>	595 x 590 x 547
<b>Dimensions of the packed product (HxWxD)</b>	760 x 710 x 650
<b>Control Panel Material</b>	without panel
<b>Door Material</b>	Glass
<b>Net weight</b>	54.3
<b>Usable volume of cavity</b>	76
<b>Cooking method</b>	Baking stone function, Bottom heat, Full width grill, Hot Air, Hot Air-Eco, Hot air grilling, Top/bottom heat, Top heat
<b>First cavity material</b>	
<b>Number of interior lights</b>	1
<b>Length electrical supply cord</b>	
<b>Interior Lights - cavity 1</b>	1
<b>Pull-out system</b>	Accessory
<b>Clock function</b>	Alarm, Off, On, timer
<b>Included accessories</b>	1 x enamel baking tray, suit, pyrolytic clean, 1 x glass pan, 1 x grill shelf
<b>Bake Element Wattages cavity 1</b>	
<b>Broil Element Wattages cavity 1</b>	3000
<b>Convection Element Wattages cavity 1</b>	2100
<b>Microwave wattage cavity 1</b>	
<b>Drawer wattage</b>	
<b>Energy efficiency rating</b>	A
<b>Energy consumption per cycle conventional - NEW (2010/30/EC)</b>	1.25
<b>Energy consumption gas oven per cycle conventional - NEW (2010/30/EC)</b>	
<b>Energy consumption per cycle forced air convection - NEW (2010/30/EC)</b>	0.83
<b>Energy consumption gas oven per cycle forced air convection - NEW (2010/30/EC)</b>	
<b>Energy efficiency index (2010/30/EC)</b>	95.4
<b>Connection rating</b>	3700
<b>Fuse protection</b>	16
<b>Voltage</b>	220-240
<b>Frequency</b>	50
<b>Plug type</b>	no plug
<b>Connecting cable type</b>	
<b>Universal Product Code</b>	
<b>Color / Material Front</b>	Anthracite
<b>Alternative colors available</b>	BO420112
<b>Energy input</b>	Electric
<b>Length of electrical supply cord (in)</b>	
<b>Required cutout/niche size for installation (in)</b>	x x
<b>Dimensions of the packed product</b>	29.92 x 25.59 x 27.95
<b>Net weight</b>	120.000
<b>Gross weight</b>	129.000
<b>Length electrical supply cord</b>	

To achieve the 550 mm installation depth, the connection cable needs to follow the slanted edge on the lower right hand corner of the housing.  
 The mains socket needs to be planned outside the built-in niche.  
 The LAN port can be found at the back on the upper right side.

#### Connection

Energy efficiency class A at a range of energy efficiency classes from A+++ to D.  
 Total connected load 3.7 KW.  
 Plan a connection cable.  
 Power consumption standby/display on 0.7 W.  
 Power consumption standby/display off 0.5 W.  
 Power consumption standby/network 1.4 W.  
 Time auto-standby/display on 20 min.  
 Time auto-standby/display off 20 min.  
 Time auto-standby/network 20 min.  
 Plan a LAN cable.

#### Color Variants

<b>BO420102</b>
<b>Full glass door in Gaggenau Anthracite</b>
<b>Width 60 cm</b>
<b>BO420112</b>
<b>Stainless steel-backed full glass door</b>
<b>Width 60 cm</b>

#### Included accessories

1 x enamel baking tray, suit, pyrolytic clean.  
 1 x glass pan.  
 1 x grill shelf.

#### Optional accessories

<b>BA016105</b>
<b>Pull-out system</b>
<b>BA026115</b>
<b>Baking tray, enamelled</b>
<b>BA036105</b>
<b>Wire rack, chromium-plated.</b>
<b>BA046117</b>
<b>Glass tray</b>
<b>BA056115</b>
<b>Heating element for baking stone and Gastronom roaster.</b>
<b>BA056133</b>
<b>Baking stone.</b>
<b>BA226105</b>
<b>Grill tray, enamelled</b>
<b>BS020002</b>
<b>Pizza paddle, set of 2.</b>
<b>GN340230</b>
<b>Gastronom roaster in cast aluminium.</b>

#### Product Variants

<b>BO421102</b>
<b>Oven 400 series</b>
<b>Full glass door in Gaggenau Anthracite</b>
<b>Width 60 cm</b>
<b>Left-hinged</b>
<b>Controls at the top</b>

